NOTES:

- 1. ALL AXLES, ROLLERS AND PIVOT POINTS ARE EQUIPPED WITH LIFE-TIME LUBRICATED BEARINGS.
- 2. LIFT TO BE PAINTED AQ STANDARD ENAMEL.
- 3. MEETS OR EXCEEDS ANSI MH29.1 STANDARD FOR INDUSTRIAL SCISSORS LIFTS.

THIS PROPOSAL DRAWING IS GENERIC BY DESIGN AND IS FOR REFERANCE ONLY. PLEASE CONTACT AUTOQUIP FOR JOB SPECIFIC APPROVAL DRAWINGS.

MODEL NO:	
MAX CAPACITY:	
LOWERED HEIGHT:	
TRAVEL:	
RAISED HEIGHT:	

POWER UNIT, CONTROLS, AND

ACCESSORIES PER QUOTATION.

" PLATFORM LENGTH-TRAVEL (2) CYLINDERS W/ **CHROME PLATED RODS AND VELOCITY FUSES** PLATFORM IN **LOWERED POSITION LOWERED HEIGHT** " BASE LENGTH

" PLATFORM WIDTH-**RAISED HEIGHT** $\triangle^{\Delta}_{\Delta}$ " BASE WIDTH— <u>Autoquip</u>.

(NOT TO SCALE)
PROPOSAL DRAWING

FLOOR MOUNTED DOUBLE PANTOGRAPH (DP) LIFT

MAINTENANCE DEVICE

QUOTE NO. ______ REV. 1, 3/12/02

© COPYRIGHT RESERVED AUTOQUIP CORPORATION FT AUTOQUIP CORP.
1058 W.INDUSTRIAL AVE.
GUTHRIE, OK 73044-1058
888-811-9876 WWW.AUTOQUIP.COM